





Mulcher conceived for very large farms and agricultural contractors. Robust machine designed for very intensive mulching, intended for mulching grass in orchards, nurseries and park maintenance, straw, maize stalks, and on fallow land. Depending on the plantation, different working widths can be set between 3,60m and 5,40m thanks to our hydraulic beam. The innovative and practical device for opening and closing the rotors is equipped

with special hitches and safety valves for transport. The 480mm diameter mulching rotor delivers maximum throughput. A heavy steel beam forms a fixed leveling point, relative to which the two rotor structure can be lifted and lowered, the two rotor overlap and can work independently of each other. It gives also better users visibility across the whole working width. The inside belt transmission allows us to approach the lateral edges as close as possible to the feet of the trees.

CHARACTERISTICS

- ► Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 450 mm.
- ► Gearbox SERRAT.
- ▶ 2 x 3 XPC side belt transmission.
- ► Forged agricultural hammers SERRAT
- ► Hammers guaranteed against breakage.
- ► GIROSTOP System.
- ▶ Supports of bearing rotor in steel.
- ► High speed and high strength bearings.

- ► Front protection curtain.
- ▶ Obturations antiwire in rotor.
- ▶ Double bearing on rear roller.
- ► Rear height-adjustable rollers Ø 210 mm.
- ▶ PTO 1.000 rpm.
- ► Hydraulic folding exclusive design by SERRAT.
- ▶ Reversible.
- ▶ Model built under EC Normative.
- ► Safety indicators visible to personnel.

ABATIBLE EVOLUTION /// ABATIBLE EVOLUTION CATALOGUE 2021

Reversible



Hydraulic folding device



/	MODEL				KG	N° BELTS TYPE							
		mm	KW-HP				A mm	A in	B mm	B in	C mm	C in	
١	T-3600	3600	52 - 70 104 - 140	16 + 16	1742	2 x 3 XPC	3700	146"	2085	82"	1220	48"	1000
١	T-4000	4000	60 - 80 112 - 150	20 + 20	1845	2 x 3 XPC	4100	161"	2085	82"	1220	48"	1000
ı	T-4600	4600	67 - 90 119 - 160	20 + 20	2110	2 x 3 XPC	4715	186"	2140	84"	1220	48"	1000
ı	T-5400	5400	82 - 110 119 - 160	20 + 20	2357	2 x 3 XPC	5515	217"	2140	84"	1220	48"	1000

OPTIONS



► With the EXTENDABLE SYSTEM we will increase the weight of 140 kgs.



► Preparation for reversible tractor



▶ Front chains




► Front gums



22310 Castejón del Puente (Huesca)-España Tfno. (+34) 974 417 830 www.serrat.com - comercial@serrat.es





The data presented in this catalog are provided for information purposes only and are not binding.