



Biogreen mulcher, in just one operation and with the usual speed is able to cut and launch the grass and branches to a deposit to remove them from the ground.

With this special application SERRAT wants to contribute to the maintenance of natural areas, roadsides and abores all. wetlands exporting the remains directly to a deposit or a trailer.

## CHARACTERISTICS

- ▶ Non-wear steel-plate chassis, thickness 8 mm.
- ▶ Rotor POLSER of Ø 600 mm.
- ▶ Gearbox SERRAT.
- ▶ 5 XPC side belt transmission.
- ▶ GIROSTOP System.
- ▶ Steel counter hammers.
- ▶ Reaction and impulse turbine with independant transmission.
- ▶ PTO 1.000 rpm.
- ▶ High speed and high strength bearings.
- ▶ Front protection curtain.
- ▶ Obturations antiwire in rotor.
- ▶ Steel worm screw Ø 300 mm.
- ▶ Supports of bearing rotor in steel.
- ▶ Forged hammers SERRAT special "grass".
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Recivering about 98% of the product from the ground



Unloading to the ground








Obturations antiwire in rotor



Lateral view. Settings on high flotation tractor



MODEL					Nº BELTS TYPE							
	mm	KW-HP				A mm	A in	B mm	B in	C mm	C in	
T-2000	2000	59 - 80 88 - 120	16	1505	5 XPC	2460	97"	1150	45"	950	37"	1000
T-2300	2300	59 - 80 88 - 120	20	1700	5 XPC	2760	109"	1150	45"	950	37"	1000

## OPTIONS

▶ Second turbine



▶ Freewheel on transmission

