



INTERPIQUET DOBLE

SEKURLAST



Double mechanical driven swing arms mower conceived to mow around trees, under fences, posts, crash barrier, vineyards, trees, etc. without any damage. Allowing in a single work process to clean two lines of plantation in an average speed of 3 km/hour. We work with a width of 6,30 meters with regard to the axis of the tractor (3,15 m in each sides).

Mechanical transmission by power take-off for tractors between 70 and 105 hp. Requiring a double effect hydraulics service for the adjustment of the air pressure and a simple effect service for the hydro pneumatic suspension.

CHARACTERISTICS

- ▶ 3 point hitch - cat. II.
- ▶ Cutting diameter of 1.200 mm.
- ▶ Cutting width of 6.200 mm - 6.500 mm.
- ▶ Length for the transport of 3.400 mm.
- ▶ 3 retractable knives in each machine.
- ▶ Air pressure adjustment (1 double effect's service).
- ▶ Pushing control by hydropneumatic suspension (adjustable).
- ▶ Lower bowl of control on the ground and rear wheels.
- ▶ Pushing control by hydro pneumatic suspension (2 hydraulics simple effect).
- ▶ PTO 540 rpm.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.









Air pressure adjustment (1 double effect's service).
Pushing control by hydro pneumatic suspension (2 hydraulics simple effect).



Control wheel of height of work.



MODEL											
					A	A	B	B	C	C	
	mm	KW-HP			mm	in	mm	in	mm	in	
T-6200	6200	78 - 105	3x2	1028	2536	100"	6200	244"	1200	47"	540
T-6500	6500	78 - 105	3x2	1032	2686	106"	6500	256"	1500	59"	540

OPTIONS

- ▶ Rubber sleeve around the plate



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.