



CHARACTERISTICS

- ► Steel-plate chassis, thickness 10 mm.
- ▶ Rotor with system RHENDUEL of Ø 450 mm.
- ▶ Power of tractor between 60 120 HP.
- ► 3 XPC side belt transmission.
- ► Treated blades.
- ► Feeder with system BRALAKC.
- ► High torque hydraulic motor reversible.
- Supports of bearing rotor in steel.

High speed and high strength bearings.

crossing with fixed palate.

- ▶ PTO 1.000 rpm.
- Double bearing on rear roller.
- ► Triple feed chain.
- Double lines of counter hammers RHENDUEL.

Mulcher with reversible hydraulic feeder, ideal for pruning of vineyard, dessert grapes, chestnut-trees, olive trees, almond-

Machine for demanding works, with need to deposit very thin remains in the area,

avoiding possible plagues and helping to

It has a rotor of crenellated cleavers,

trees, citrus fruits, walnuts, hazels, etc.

For tractors between 60 and 120 HP.


their elimination, for later processes.

- Model built under EC Normative.
- Safety indicators visible to personnel.

Ferrot LLLL







OPTIONS



Freewheel on sleeve



Fordward position

Tfno. (+34) 974 417 830




22310 Castejón del Puente (Huesca)-España

www.serrat.com - comercial@serrat.es

CATALOGUE 2021

CATALOGUE 2021

Triple feed chain



N° BELTS TYPE	B C C C C C C C C C C C C C C C C C C C						
	A mm	A in	B mm	B in	C mm	C in	
3 XPC	1835	72"	1197	47"	1185	47"	1000
3 XPC	2037	80"	1197	47"	1185	47"	1000
3 XPC	2235	88"	1197	47"	1185	47"	1000



Reverse position



The data presented in this catalog are provided for information purposes only and are not binding.

89