



SPLINTER 450



Mulcher with reversible hydraulic feeder, ideal for pruning of olive trees, citrus trees and nuts.

Adapted to crush residues from 8-10 cm of diameter, with the rotor SPLINTER of SERRAT which is adapted for tractors between 70 and 140 HP.

It works in reverse to preserve the tractor for doesn't pass at the top of the branches.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 8 mm.
- ▶ Rotor with SPLINTER technology of Ø 450 mm.
- ▶ Gearbox SERRAT for tractors between 70 and 140 HP.
- ▶ 3 XPC side belt transmission.
- ▶ Treated blades.
- ▶ Feeder with system BRALAKC.
- ▶ High torque hydraulic motor reversible.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ PTO 540 (110 HP) or 1.000 rpm (140 HP).
- ▶ Double bearing on rear roller.
- ▶ Triple feed chain.
- ▶ 2 lines of counter knives screwed in.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



2 lines of counter knives screwed in



Rotor SPLINTER Technology



MODEL	mm	KW-HP			N° BELTS TYPE							
						A mm	A in	B mm	B in	C mm	C in	
T-1600	1600	52 - 70 82 - 110	66	1108	3 XPC	1855	73"	1235	49"	1215	48"	1000
T-1800	1800	60 - 80 82 - 110	78	1200	3 XPC	2055	81"	1235	49"	1215	48"	1000
T-2000	2000	67 - 90 82 - 110	84	1286	3 XPC	2255	81"	1235	49"	1215	48"	1000



TDF 540 rpm -> 110 HP; TDF 1.000 rpm -> 140 HP

Steering Wheels



OPTIONS



▶ Freewheel on sleeve



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.