



Mulcher designed for tractors between 60 HP to 120 HP for the maintenance of vegetable mantle and for the elimination of remains of pruning up to 8 cm.

Special configuration for frontal works.


CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 450 mm.
- ▶ Gearbox SERRAT.
- ▶ 3 XPC side belt transmission.
- ▶ Forged agricultural hammers SERRAT.
- ▶ Hammers guaranteed against breakage.
- ▶ Three lines of steel counter hammers.
- ▶ GIROSTOP System.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Rear gum over the roller.
- ▶ Double direction of rotation in the rotor.
- ▶ Double bearing on rear roller.
- ▶ Rear height-adjustable roller Ø 180/210 mm.
- ▶ PTO 1.000 rpm.
- ▶ Rear hydraulic hood with sieve.
- ▶ Long skid shoes.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



System antiwire in rotor



MODEL	 mm	 KW-HP		 KG	Nº BELTS TYPE							
						A mm	A in	B mm	B in	C mm	C in	
T-1600	1600	45 - 60 90 - 120	12	720	3 XPC	1825	72"	1035	41"	995	39"	1.000
T-1800	1800	45 - 60 90 - 120	16	785	3 XPC	2025	80"	1035	41"	995	39"	1.000
T-2000	2000	45 - 60 90 - 120	16	875	3 XPC	2225	88"	1055	42"	995	39"	1.000
T-2300	2300	45 - 60 90 - 120	20	1270	3 XPC	2525	99"	1385	55"	1060	42"	1.000



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.