



CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 6 mm.
- ▶ Rotor with system RHENDUEL of Ø 280 mm.
- ▶ Power of tractor between 50 70 HP.
- ► 4 XPB side belt transmission.
- ► Treated blades.
- ► Feeder with system BRALAKC.
- ► High torque hydraulic motor reversible.
- Supports of bearing rotor in steel.

- High speed and high strength bearings.
- ▶ PTO 540 rpm.

50 and 70 HP.

- Double bearing on rear roller.
- Double feed chain.
- Gearbox with freewheel included.
- Double lines of counter hammers RHENDUEL.

Mulcher with reversible hydraulic feeder, ideal for pruning of vineyard, dessert grapes,

- Model built under EC Normative.
- Safety indicators visible to personnel.

Feeder Bralakc



MODEL				O KG	N° BELTS TYPE							
	mm	KW-HP				A mm	A in	B mm	B in	C mm	C in	
T-1200	1200	37 - 50 52 - 70	4X6	618	4 XPB	1375	54"	1312	51"	850	33"	540
T-1400	1400	45 - 60 52 - 70	4X7	670	4 XPB	1575	62"	1312	51"	850	33"	540



Ruota libera nel

manicotto



Reverse or forward positions



22310 Castejón del Puente (Huesca)-España Tfno. (+34) 974 417 830 www.serrat.com - comercial@serrat.es



CATALOGUE 2021

CATALOGUE 2021







► Rear wheels

The data presented in this catalog are provided for information purposes only and are not binding.

85