







Mulcher with reversible hydraulic feeder, ideal for pruning of olive trees, citrus trees and nuts.

to crush residues 8-10 cm of diameter, with the rotor ÓCLAME of SERRAT which is adapted for tractors between 90 and 140 HP.

It works in reverse to preserve the tractor for doesn't pass at the top of the branches.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor ÓCLAME of Ø 550 mm.
- ► Gearbox SERRAT for tractors between 90 and 140 HP.
- ▶ 4 XPC side belt transmission.
- ► Treated blades.
- ► Feeder with system BRALAKC.
- ► High torque hydraulic motor reversible.

- ► Supports of bearing rotor in steel.
- ► High speed and high strength bearings.
- ▶ PTO 1.000 rpm.
- ▶ Double bearing on rear roller.
- ► Triple feed chain.
- ▶ Model built under EC Normative.
- ► Safety indicators visible to personnel.



Feeder Bralakc



Rotor Óclame Technology



	MODEL	N° BELTS TYPE						B A					
_		mm	KW-HP				A mm	A in	B mm	B in	C mm	C in	
	T-1600	1600	67 - 90 104 - 140	66	1312	4 XPC	1850	73"	1275	50"	1235	49"	1000
	T-1800	1800	78 - 105 104 - 140	78	1421	4 XPC	2050	81"	1275	50"	1235	49"	1000
	T-2000	2000	89 - 120 104 - 140	84	1520	4 XPC	2250	89"	1275	50"	1235	49"	1000

OPTIONS



► Freewheel on sleeve



► Steering Wheels



22310 Castejón del Puente (Huesca)-España Tfno. (+34) 974 417 830 www.serrat.com - comercial@serrat.es





The data presented in this catalog are provided for information purposes only and are not binding.