



Soil preparation machine up to a depth of 40 cm, for tractors between 180 - 250 HP. It mulchs the stumps of old plantations, leaving a soft ground for the next plantation.

### CHARACTERISTICS






- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor FIXE TOP of Ø 900 mm.
- ▶ Gearbox with freewheel included.
- ▶ Double synchronous belt transmission.
- ▶ Supports of bearing rotor in steel.
- ▶ Oscillating bearings of double row of rollers.
- ▶ Double ploughshare for opening the land.
- ▶ PTO 1.000 rpm.
- ▶ Front skid shoes.
- ▶ Rear hydraulic hood.
- ▶ Internal reinforcements in anti-wear chassis.
- ▶ System antiwire in rotor.
- ▶ Compact drive cover.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Rear hidraulic hood  
Compact drive cover

FIXE TOP System



MODEL	 mm	 KW-HP	 KG	Nº BELTS TYPE								
	A mm	A in	B mm	B in	C mm	C in						
T-1100	1100	132 - 180 186 - 250	32	2700	2 Synchronous	1100	43"	1730	68"	1585	62"	1000

### OPTIONS

- ▶ Side shift

