

serrat



Mulcher designed for tractors between 20 HP to 40 HP for the maintenance of vegetable mantle and for the elimination of remains of pruning up to 30 mm.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 4 mm.
- ▶ Tubular rotor of Ø 350 mm.
- ▶ Gearbox with freewheel included.
- ▶ 3 XPB side belt transmission.
- ▶ Forged hammers SERRAT.
- ▶ 2 lines of counter knives screwed.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Turret to be hooked in several positions.
- ▶ PTO 540 rpm.
- ▶ Double bearing on rear roller.
- ▶ Rear height-adjustable roller Ø 140 mm.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Detail of the roller



MODEL	mm	KW-HP	kg	Nº BELTS TYPE	Diagram							
					A mm	A in	B mm	B in	C mm	C in		
T-1200	1200	15 - 20 30 - 40	16	260	3 XPB	1276	50"	895	35"	828	33"	540
T-1400	1400	18 - 25 30 - 40	16	275	3 XPB	1476	58"	895	35"	828	33"	540
T-1600	1600	26 - 35 30 - 40	20	295	3 XPB	1676	66"	895	35"	828	33"	540

OPTIONS



▶ Rear gum




▶ Hydraulic side shift



▶ Front adjustable skid shoes only for straight side

serrat

Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tfno. (+34) 974 417 830
www.serrat.com - comercial@serrat.es



The data presented in this catalog are provided for information purposes only and are not binding.