



Mulcher of hammers, for the elimination of remains of pruning up to 80 mm and maintenance of vegetable mantle. Ideal for the regeneration of meadows and grassland.

Rotor POLSER of 450-500 mm of diameter. Excellent results in industrial gardening and maintenance of borders.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 450/500 mm.
- ▶ Gearbox SERRAT.
- ▶ 3 XPC side belt transmission.
- ▶ Forged agricultural hammers SERRAT.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Front protection curtain.
- ▶ System antiwire in rotor.
- ▶ Double bearing on rear roller.
- ▶ Rear height-adjustable roller Ø 180 mm (210 mm from T-2300).
- ▶ PTO 540 rpm (1,000 rpm from T-2500).
- ▶ Rear roller cleaner.
- ▶ Steel counter hammers.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



System antiwire in rotor




MODEL	mm	KW-HP	KG	Nº BELTS TYPE	Diagram								
					A mm	A in	B mm	B in	C mm	C in			
450 POLSER	T-1400	1400	44 - 60 88 - 120	12	640	3 XPC	1570	62"	1205	47"	950	37"	540
	T-1600	1600	48 - 65 88 - 120	12	678	3 XPC	1790	70"	1205	47"	1040	41"	540
	T-1800	1800	51 - 70 88 - 120	16	730	3 XPC	1990	78"	1205	47"	1040	41"	540
	T-2000	2000	55 - 75 88 - 120	16	782	3 XPC	2190	86"	1205	47"	1040	41"	540
	T-2100	2100	59 - 80 88 - 120	16	802	3 XPC	2290	90"	1205	47"	1040	41"	540
	T-2300	2300	63 - 85 88 - 120	20	889	3 XPC	2490	98"	1205	47"	1040	41"	540
500 POLSER	T-2500	2500	70 - 95 88 - 120	20	1022	3 XPC	2690	106"	1290	51"	1320	52"	1000
	T-2800	2800	74 - 100 88 - 120	24	1105	3 XPC	2990	118"	1290	51"	1320	52"	1000

OPTIONS

▶ Rear wheels



▶ Freewheel



▶ Front chains



▶ Front adjustable skid shoes



▶ Front wheels

▶ Inclined side belt protection



▶ Rear tine retainers

▶ Super hydraulic side shift V2

▶ ETT

