Se110t INTERPIQUET DOBLE

SEKURLAST





Double mechanical driven swing arms mower conceived to mow around trees, under fences, posts, crash barrier, vineyards, trees, etc. without any damage. Allowing in a single work process to clean two lines of plantation in an average speed of 3 km/h. We work with a width of 6,30 m with regard to the axis of the tractor (3,15 m in each sides). Mechanical transmission by power

take-off for tractors between 70 and 105 HP. Requiring a double effect hydraulics service for the adjustment of the air pressure and a simple effect service for the hydro pneumatic suspension.

CHARACTERISTICS

- ▶ 3 point hitch cat. II.
- ► Cutting diameter of 1,200 mm.
- ► Cutting width of 6,200 mm 6,500 mm.
- ► Length for the transport of 3,400 mm.
- ▶ 3 retractable knives in each plate.
- ► Air pressure adjustment (1 double effect's service).
- ► Pushing control by hydropneumatic suspension (adjustable).

- ▶ Lower bowl of control on the ground and rear wheels.
- ► Pushing control by hydro pneumatic suspension (2 hydraulics simple effect).
- ▶ PTO 540 rpm.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Pushing control by hydropneumatic suspension (adjustable) Hydraulic recovery control (adjustable)





Height adjustable rear wheel



MODEL					KG							
_		mm	KW-HP			A mm	A in	B mm	B in	C mm	C in	
	T-6200	6200	51 - 70 78 - 105	3x2	1028	2536	100"	6200	244"	1200	47"	540
	T-6500	6500	51 - 70 90 - 105	3x2	1032	2686	106"	6500	256"	1500	59"	540

OPTIONS

▶ Double movable wheels









The data presented in this catalog are provided fo information purposes only and are not binding.