



EVOLUTION REVERSIBLE SIDE SHIFT

450 POLSER 500 POLSER GIROSTOP >



CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 10 mm.
- ▶ Rotor POLSER of Ø 450/500 mm.
- ▶ Gearbox SERRAT.
- ▶ 3 XPC side belt transmission.
- ▶ Forged agricultural hammers SERRAT.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Front protection curtain.

- ▶ System antiwire in rotor.
- ▶ Double bearing on rear roller.
- ▶ Rear height-adjustable roller Ø 180 mm (210 mm from T-2300).
- ▶ PTO 540 rpm (1,000 rpm from T-2500).
- ▶ 1,000 rpm for front PTO.
- ▶ Rear roller cleaner.
- ▶ Steel counter hammers.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



System antiwire in rotor



		MODEL		mm	KW-HP	KG	Nº BELTS TYPE	A mm-in	B mm-in	C mm-in		
450 POLSER	500 POLSER	T-1600	T-1800									
		T-2000	2000	44 - 60 88 - 120	48 - 65 88 - 120	16	810	3 XPC	1790-70"	1450-57"	950-37"	540
		T-2300	2300	51 - 70 88 - 120	59 - 80 88 - 120	16	916	3 XPC	1990-78"	1450-57"	950-37"	540
		T-2500	2500	66 - 90 88 - 120	74 - 100 88 - 120	20	1023	3 XPC	2190-86"	1450-57"	950-37"	540
		T-2800	2800	74 - 100 88 - 120	88 - 120	24	1152	3 XPC	2490-98"	1450-57"	980-39"	1000
									2690-106"	1450-57"	980-39"	1000
									2990-118"	1450-57"	980-39"	1000

OPTIONS

- ▶ Rear wheels
- ▶ Freewheel
- ▶ Green
- ▶ Rounded side
- ▶ Gearbox 1.000 RPM for front PTO
- ▶ Rear tine retainer
- ▶ Front adjustable skid shoes
- ▶ Reinforced roller
- ▶ Front chains
- ▶ Front wheels
- ▶ Super hydraulic side shift



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tel. (+34) 974 417 830
www.serrat.com - comercial@serrat.com

