



Mulcher for the mixed utilization in remains of crop of maize, sorghum, sunflower, wheat, barley, etc. As well as, in the preparation for the dried one of herbaceous cultures (ray grass).

In incorporates hydraulic rear gate and turn able nozzles to scalter fresh straw. Rotor POLSER of 650 mm of diameter, equipped with hammers.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 8 mm.
- ▶ Rotor POLSER of Ø 650 mm.
- ▶ Gearbox SERRAT power up to 150 HP.
- ▶ 4 XPC side belt transmission.
- ▶ Stamped hammers.
- ▶ GIROSTOP system into the bolt of the hammer.
- ▶ Supports of bearing rotor in steel.
- ▶ High speed and high strength bearings.
- ▶ Front protection curtain.
- ▶ System antiwire in rotor.
- ▶ Interchangeable counter hammers.
- ▶ Rear roller Ø 210 mm.
- ▶ PTO 1,000 rpm.
- ▶ Rear hydraulic hood.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



Rear hydraulic hood




System antiwire in rotor



Rear roller Ø 210 mm



MODEL					Nº BELTS TYPE				
						A	B	C	
	mm	KW-HP		KG		mm-in	mm-in	mm-in	
T-2300	2300	74 - 100 112 - 150	24	1255	4 XPC	2545-100"	1750-69"	1200-47"	1000
T-2500	2500	74 - 100 112 - 150	24	1310	4 XPC	2745-108"	1750-69"	1200-47"	1000
T-2800	2800	88 - 120 112 - 150	24	1395	4 XPC	3045-120"	1750-69"	1200-47"	1000
T-3200	3200	96 - 130 112 - 150	32	1527	4 XPC	3445-136"	1750-69"	1200-47"	1000

OPTIONS



Front adjustable skid shoes



Adjustable nozzle



Front chains




Adjustable wheels

- ▶ Double geardrives
- ▶ Freewheel



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tel. (+34) 974 417 830
www.serrat.com - comercial@serrat.com



The data presented in this catalog are provided for information purposes only and are not binding.