



Heavy-duty high body mulcher conceived for very large farms and agricultural contractors. Robust machine designed for very intensive mulching, intended for mulching grass in park maintenance, straw, maize stalks, and on fallow land. Composition for big tractors reaching a working width of 9.5 meters with a front machine

of 3 m of working width avoiding to tread on the material to mulch. The innovative and practical device for opening and closing the rotors is equipped with special hitches and safety valves for transport. The 600 mm diameter mulching rotor delivers maximum throughput. A heavy steel beam forms a fixed leveling point, relative to which the two rotor structure can be lifted and lowered, the two rotor can work independently of each other. It gives also better users visibility across the whole working width. The inside gearboxes transmission allows us to approach the lateral edges as close as possible to the feet of the trees and towards the field edge.

CHARACTERISTICS

- ▶ Steel-plate chassis, thickness 8 mm.
- ▶ Rotor POLSER of Ø 600 mm.
- ► Gearbox SERRAT.
- ► Frontal machine 4 XPC belt transmission.
- ► Forged agricultural hammers SERRAT.
- GIROSTOP system into the bolt of the hammer.
- Supports of bearing rotor in steel.
- ► High speed and high strength bearings.
- ► Front protection curtain.
- System antiwire in rotor.

- Double bearing on rear roller.
- Rear height-adjustable rollers.
- ▶ PTO 1,000 rpm.
- Hydraulic folding exclusive design by SERRAT.
- ► HIDRAHELP.
- ▶ Rear roller Ø 280 mm.
- ► Freewheel.
- ▶ Direct cardan rear machine.
- Composition of two machines.
- Model built under EC Normative.
- Safety indicators visible to personnel.






Hidrahelp









F.R.S.: Frontal Reversible Shide Shift





Hydraulic folding exclusive design by SERRAT





BELTS YPE				
	A mm-in	B mm-in	C mm-in	
rdan	8450-333"	1300- 51"	1346-53"	1000
rdan	9642-380"	1300- 51"	1346-53"	1000
KPC	3237-127"	1470-58"	1242-49"	1000

he data presented in this catalog are provided f formation purposes only and are not binding.

59