




Mechanical driven swing arm mower can be used to mow around trees, posts, crash barrier, etc. Without any damage.

Mechanical transmission by power take-off for tractors between 40 and 100 HP.

Requiring a double effect hydraulic's service for the slope and a simple effect service for the hydropneumatic suspension.

CHARACTERISTICS

- ▶ 3 point hitch - cat. II.
- ▶ Cutting width of 1,200 mm (47 inches).
- ▶ Backwardation from the axis of the tractor of 3,100 mm (122 inches).
- ▶ Lenght for the transport of 3,000 mm (118 inches).
- ▶ 3 retractable knives.
- ▶ Mechanical transmission by power take-off.
- ▶ Pushing control by hydropneumatic suspension (adjustable).
- ▶ Hydraulic recovery control (adjustable).
- ▶ Hydraulic location according to the necessity activated from the tractor (1 double effect's service).
- ▶ PTO 540 rpm.
- ▶ Rubber sleeve around the plate.
- ▶ Lower bowl of control on the ground.
- ▶ Height adjustable rear wheel.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.









Pushing control by hydropneumatic suspension (adjustable)
Hydraulic recovery control (adjustable)



Height adjustable rear wheel



MODEL	 mm	 KW-HP		 KG				
					A mm-in	B mm-in	C mm-in	
INTERPIQUET	3100	30 - 40 74 - 100	3	450	3000-118"	3100-122"	1200-47"	540

OPTIONS

- ▶ Protection for road
- ▶ DIR: vertical wheel + protection



Carretera nacional 240 km. 149,3
22310 Castejón del Puente (Huesca)-España
Tel. (+34) 974 417 830
www.serrat.com - comercial@serrat.com



The data presented in this catalog are provided for information purposes only and are not binding.