



Soil preparation machine up to a depth of 250 mm, for tractors between 80 - 130 HP. Transforms forest land, with stumps and rocks, in land for cultivation avoiding accidents in later processes.

CHARACTERISTICS







- ▶ Steel-plate chassis, thickness 8 mm.
- ▶ Rotor FIXE TOP of Ø 470 mm.
- ▶ Gearbox SERRAT for 130 HP.
- ▶ 2 x 4 XPC belt transmission.
- ▶ Supports of bearing rotor in steel.
- ▶ Oscillating bearings of double row of rollers.
- ▶ PTO 1,000 rpm.
- ▶ Rear hydraulic hood.
- ▶ Protection chains.
- ▶ Chassis internal reinforcements, thickness 10 mm.
- ▶ System antiwire in rotor.
- ▶ Compact drive cover.
- ▶ Rear roller into the hood.
- ▶ Soil preparation machine up to a depth of 250 mm.
- ▶ Model built under EC Normative.
- ▶ Safety indicators visible to personnel.



1. Rear hydraulic hood
2. Compact drive covers
3. Rear roller into the hood

FIXE TOP System



MODEL					Nº BELTS TYPE				
	mm	KW-HP				A mm-in	B mm-in	C mm-in	
T-1600	1600	59 - 80 97 - 130	34	1555	2 x 4 XPC	2000-79"	1576-62"	1072-42"	1000
T-1800	1800	59 - 80 97 - 130	38	1615	2 x 4 XPC	2200-87"	1576-62"	1072-42"	1000
T-2000	2000	59 - 80 97 - 130	44	1675	2 x 4 XPC	2400-94"	1576-62"	1072-42"	1000

*For working in depth it is recommended that the tractor has a Creeper or Vario.

